

Walls Protect you from the Nature
Protect them from Nature with

ZYDEX PRIMER

One-Step 360⁰ Waterproofing & Bonding Solution



Water
(TDS<1000 ppm)

Zycosil Plus
(100% Silane)

Zycoprime Plus
(Acrylic Bonder)

Just Spray or use Roller Brush

Vertical Walls (Exterior / Interior)

SINGLE APPLICATION THREE COMPONENT SYSTEM

Penetrates into the walls | Waterproofs and Bonds chemically | Excellent adhesion to water based wall finishes

Zycoprime™+ (2 Parts) ZP 35 - Acrylic Bonding Agent

TECHNICAL SPECIFICATIONS

Appearance	Milky white free flowing liquid
Viscosity at 25°C	10 – 100 cps
Specific gravity range	1.03 ± 0.02
Flash Point	Water Based Non Flammable
Odour	Low Odour
Solubility in water	Complete
pH	6.5 to 8
Diluent	Clean Potable water (TDS <1000 ppm)

DESCRIPTION

Zycoprime Plus forms a water resistant cementitious bonding coat and reduces porosity of the structure. It acts as an excellent bonding agent for improving adhesion of concrete / plaster / paint, on Zycosil Plus treated surfaces.

ZYCOSIL®+ (1 Part)

Penetrative Waterproofing

TECHNICAL SPECIFICATIONS

Appearance	Light Pale Yellow clear liquid
Viscosity at 25°C	20 – 100 cps
Specific gravity range	0.91 ± 0.02
Flash Point	12 °C
Odour	Low Odour
Solubility in water	Complete
pH	Approx. 6 ± 1
Diluent	Clean Potable water (TDS <1000 ppm)

DESCRIPTION

ZYCOSIL + is a 100% Reactive Organosilane Nano-sealer which becomes integral part of the structure itself. ZYCOSIL + is water dilutable, safe, sprayable and easy to apply.

Water (TDS < 1000 ppm) (20 Parts)

Mix these three from bottom to top Beginning with water to Zycoprime Plus

SURFACE PREPARATION Clean and smoothen the plaster / concrete surface of all dust, foreign matters, loose materials or any deposits of contamination by wire brush / air blower / grinder / high pressure water jet.

STORAGE AND SHELF LIFE Store in a shaded area away from direct sunlight, between 5-45 °C. Protect from extreme temperatures. Shelf life is 24 months when stored as recommended.

PACKING 20 Ltr. Carboys

DISCLAIMER

Whilst the information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

Zydex®

Zydex Industries

Zydex House, 61 Gotri Sevasi-Road, Sevasi, Vadodara - 391 101

Tel : +91 265 3312000 ● Fax : +91 265 3312111 ● Toll Free No. : 1800-3000-120

E-mail : zycosil@zydexindustries.com www.zydexindustries.com